

# Scaffolding Components


Access Solutions also supplies a large range of scaffolding components such as castors, screw & swivel jacks and braces to add onto existing compatible scaffolds.

In addition to these existing scaffolding configurations, if your project requires something out of the ordinary, let Access Solutions design and construct a unique scaffolding structure to suit your particular specifications. Scaffolding is designed in accordance with AS/NZS 1576-1995 "Australian/New Zealand Standard Scaffolding" and is rated light duty (225kg) and medium duty (450kg) load rating.

**Castors** Large 200mm (8") Castors move easily over rough terrain with a load rating of 900kg. The lever locking action automatically centres the wheel under the upright for maximum stability.




**Platforms** The platforms have been tested to withstand twice the rated safe working load. They are lightweight and fitted with weatherproof ply making assembly and use at any height much safer.



**Adjustable Outriggers** Adjustable Outriggers are optional and reduce the need for wide scaffolds. They can be used to increase the stability of any freestanding tower.



**Jacks** Screw Jacks & Swivel Base Jacks can also be used as firm footings on non-mobile applications. All Screw Jacks & Castor Shafts have recessed threads to reduce jamming in scaffold frames.



**Braces** Self locking spring loaded brace hooks have a simple action and require no priming. They are colour coded for easy identification and can be locked into place in one simple operation.



**Toe Boards** Quick fitting, Timber or lightweight Aluminum Toeboards



**Castor Shafts & Screw Jacks** All Castor Shafts & Screw Jacks have Graphite Nylon protection end caps for easy entry into frame.



**Access Ladders** Specifically designed for mobile towers. Ladders feature two rigid stay arms. Safety hatches are provided on all work platforms for easy access.




**Frames** Each frame is manufactured from high strength Aluminum with a 2mm wall thickness and all joints are welded for maximum strength and durability.



**Anti-Lock Spigots** Anti-Lock Spigots are replaceable Graphite Nylon and automatically engage locking clip. Spigots remove easily from frames.



**Access Platforms** Side opening hatches for safe and easy access with easy release locks are able to be provided on all working levels.



**Component Lengths**  
Platform lengths: 1.2m, 1.9m, 2.4m, 3.0m.  
Brace Lengths: 1.2m, 1.9m, 2.4m, 3.0m.  
Frame widths: 0.7m, 1.2m, 1.9m, 2.4m, 3.0m.  
Frame heights: 1.2m, 1.6m, 2.0m.

**ACCESS SOLUTIONS**

**KIWISCAF**

FREEPHONE 0800 653 343 | [www.accesssolutions.co.nz](http://www.accesssolutions.co.nz)