

Performance

Platform Height—Elevated	5.64 m
Platform Height—Lowered	1.0 m
Platform Capacity	230 kg
Capacity on Deck Extension	120 kg
Lift/Lower Time	25/26 sec
Maximum Drive Height	5.64 m
Weight	1,588 kg
Ground Bearing Pressure	8.4 kg/cm ²
Drive Speed	
Lowered	4 km/h
Elevated	0.8 km/h
Gradeability	25%
Turning Radius	
Inside	0.6 m
Outside	2.2 m

Standard Specifications

Tyres

- Solid, Non-Marking

Brakes

- Electric, Friction on Drive Wheels
- Guard Rail Type--Fixed

Power Source

Batteries	4 x 6V, 220 AH
Charger	25 Amp
Drive	24V DC
Pump	3.2 cc/rev @ 2,300 psi (178 kg/cm ²)

Hydraulic System

Capacity	5 L
----------	-----

Standard Features

- Proportional Controls
- Industry Leading Duty Cycles
- Battery Condition Indicator
- Automatic Traction Control (ATC)
- All Motion Alarm
- 25 Amp Automatic SCR Charger
- Horn
- Hourmeter
- Flashing Amber Beacon
- Lubrication-Free Scissor Arm Bushings
- Tilt Alarm and Light
- LSS – Load Sensing System
- Forklift Pockets
- Moveable, Removable Platform Control
- Manual Descent Pull Cable
- Mechanized Pothole Protection
- Scissor Maintenance Prop
- 70 cm Roll-Out Deck Extension

Accessories & Options

- AC Power to Platform
- Anti-Vandal Control Box Covers
- Squawker Motion Alarm
- 220 Amp-Hour AGM Batteries
- IP65 Fixed Charger Inlet
- Special Hydraulic Oils



Dimensions

All dimensions are approximate.

